


## Geberit Duofix frame for wall-hung WC, 79 cm, with low-height concealed cistern



Example image



### Application purposes

- For drywall construction
- For installation in bathroom furniture
- For installation in part-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For floor constructions 0–20 cm

### Characteristics

- Self-supporting frame, powder-coated
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- Galvanized feet

### Scope of delivery

- 2 threaded rods M12
- Fastening material
- Connection bend 90° made of PE-HD, ø 90 mm

### To order additionally

- Geberit remote flush actuation type 01, pneumatic, for dual flush, furniture actuator
- Geberit remote flush actuation type 10, pneumatic, for dual flush, furniture actuator

- Feet adjustable 0–20 cm
- With large foot plates for raised power supply in floors
- Connection bend can be mounted without tools at different depths, adjustable range 45 mm
- Fastening for connection bend, sound-absorbing
- Flush actuation pneumatic
- Flush pipe connection with compression joint
- Water supply connection on the bottom left

### Technical data

|                                      |             |
|--------------------------------------|-------------|
| Flow pressure                        | 0.1-10 bar  |
| Maximum operating temperature, water | 25 °C       |
| Flush volume, factory setting        | 5.8 and 3 l |

| Art. no.     | B       | H     | T            |
|--------------|---------|-------|--------------|
| 111.207.00.2 | 46.5 cm | 79 cm | 19.5–31.5 cm |

### Accessories

- Geberit set of support brackets for WC ceramic appliances with small contact surfaces



- For furniture with an internal dimension of 465 mm wide, the item can not be used with side plinths
- Includes extension brackets taking the depth up to 335 mm
- This frame has been especially designed for use with furniture and furniture clips only
- For installation in bathroom furniture with full length front panel (not for use with front plinths)
- This frame must not be installed behind the wall
- The cistern can be operated with used water (rainwater) provided it is passed through a filter system first